

# Charging cable Mode3 Typ2 20A 3ph 7,5m



| Part number        | 08 91 409 0106 A0                      |
|--------------------|--|
| Specification      | Charging cable Mode3 Typ2 20A 3ph 7,5m |
| HARTING eCatalogue | https://b2b.harting.com/08914090106A0  |

Image is for illustration purposes only. Please refer to product description.

#### Identification

| Element       | Charging cable                    |
|---------------|-----------------------------------|
| Specification | Straight                          |
| Charging mode | Mode 3                            |
| Connector 1   | Type 2 Female (Vehicle side)      |
| Connector 2   | Type 2 Male (infrastructure side) |

#### Version

| Cable length              | 7.5 m  |
|---------------------------|--|
| Termination method        | Crimp termination                                      |
| Core structure            | 5x 2.5 mm² + 0.5 mm²                                   |
| Number of phases          | 3  |
| Number of contacts        | 7  |
| Number of signal contacts | 2  |
| Number of power contacts  | 5  |
| Contact configuration     | Signal: CP, PP<br>Power: L1, L2, L3, N, PE             |
| Details                   | Also available with customer specific logo on request. |

### Technical characteristics

| Rated current (signal) | 2 A  |
|------------------------|------|
| Rated voltage (signal) | 30 V |
| Rated current (power)  | 20 A |



#### Technical characteristics

| Rated voltage (power)                  | 480 V   |
|--|---|
| Type of current                        | AC  |
| Charging power                         | 11 kW   |
| Coding resistance                      | 680 Ω between PE and PP                                 |
| Ambient temperature                    | -30 +50 °C in operation<br>-40 +80 °C storage/transport |
| Air pressure                           | ≥540 hPa ≈ 5000 m                                       |
| Insertion force                        | <100 N  |
| Withdrawal force                       | <100 N  |
| Mating cycles                          | ≥10,000   |
| Degree of protection acc. to IEC 60529 | IP44  |
| Cable diameter                         | 12.8 mm ± 0.4 mm  |
| Minimum bending radius                 | 9x Cable diameter (repeated bending)                    |
| Conductor resistance @ 20 °C           | ≤7.98 Ω/km @ 2.5 mm²<br>≤39 Ω/km @ 0.5 mm²              |

## Material properties

| Material (insert)                         | Polyamide (PA)                   |
|---|----------------------------------|
| Colour (insert)                           | Black                            |
| Material (contacts)                       | Copper alloy                     |
| Surface (contacts)                        | Silver plated                    |
| Material (hood/housing)                   | Polyamide (PA)                   |
| Colour (hood/housing)                     | Black                            |
| Material (cover)                          | Thermoplastic polyurethane (TPU) |
| Material (cable)                          | TPE-U                            |
| Colour (cable)                            | Black                            |
| Material flammability class acc. to UL 94 | V-0                              |
|   |                                  |

## Specifications and approvals

| Specifications | IEC 62196-2<br>IEC 62893 |
|----------------|--------------------------|
| Approvals      | VDE                      |

## Commercial data

| Packaging size | 1 |  |
|----------------|---|--|
|----------------|---|--|

Product data sheet 08 91 409 0106 A0 Charging cable Mode3 Typ2 20A 3ph 7,5m



## Commercial data

| Net weight                     | 4 kg                               |
|--------------------------------|------------------------------------|
| Country of origin              | Romania                            |
| European customs tariff number | 85444991                           |
| eCl@ss                         | 27144705 Charging cable E-Mobility |