

# Akku-Line



## LED Arbeitsleuchte FLEX POWER 10

- Mit Powerbank
- 300° klappbarer Standfuß
- 360° beweglicher Leuchtkörper
- Inkl. USB-Ladekabel
- Energieeffizienzklasse: A+
- Schutzart: IP 20
- Leuchtmittel: 2 x 5 W SMD LEDs
- 2 x 500 Lumen, 6500 Kelvin
- Abmessungen (BxHxT): ca. 200 x 50 x 140 mm (eingeklappt); ca. 230 x 200 x 50 mm (ausgeklappt)
- Vorschaltgerät: LED-Treiber
- Lebensdauer: 30.000 h
- Leuchtdauer: 4 h (bei höchster Helligkeitsstufe)
- Stufenschalter: 50 % oder 100 % Leuchtkraft
- Farbwiedergabeindex RA:  $\geq 70$
- Abstrahlwinkel: 80°
- Schutzklasse: IIII
- Lithium-Polymerakku: 3,7 V DC / 5000 mAh / 18,5 Wh
- USB: Micro IN 5 V DC / max. 1 A; USB OUT 5 V DC / max. 1 A
- Umgebungstemperatur: -20° C bis +50° C

## LED worklight FLEX POWER 10

- with powerbank
- 300° foldable base
- 360° foldable light fixture
- USB cable included
- energy efficiency category: A+
- protection type: IP 20
- illuminant: 2 x 5 W SMD LEDs
- 2 x 500 Lumen, 6500 Kelvin
- dimensions (WxHxD): appr. 200 x 50 x 140 mm (folded); appr. 230 x 200 x 50 mm (folded out)
- electronic control gear: LED-driver
- lifetime: 30,000 h
- light ON time: 4 h (at the highest brightness level)
- tap changer: 50 % or 100 % luminous power
- colour rendering index RA:  $\geq 70$
- transmission angle: 80°
- protection class: IIII
- lithium polymer rechargeable battery: 3.7 V DC / 5000 mAh / 18.5 Wh
- USB: Micro IN 5 V DC / max. 1 A; USB OUT 5 V DC / max. 1 A
- ambient temperature: -20° C up to +50° C

IP20

LED

2620011610

grau-orange  
grey-orange

Karton  
box

VE 3  
PU 3

