

LogiLink®



Smoke Detector

With Replaceable 9 V Battery

Art. No.: SC0015

Complies with
EN 14604
Standard

 **Replaceable**
9 V Battery

Make Your Life Safer

This smoke detector with replaceable 9 V battery has photoelectric sensor which is optimized to detect even slow smoldering fires. Alarm also features a loud 85 dB alarm, easy mounting bracket, a single test/silence button, and an end-of-life signal so you know when to replace the battery. For maximum protection and the ultimate in assurance, you can depend on Logilink's Smoke Detector to secure what matters most in life.

 **85dB Alarm**  **Silent Mode**  **LED Indicator**  **Low Battery Warning**  **Easy to Install**



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.





Highly Accurate & Responsive

Features photoelectric technology; the smoke detector responds to hazardous smoke quicker than traditional detectors. With an 85 dB alarm and a rapid flashing indicator, the alarm ensures complete protection by giving you enough time to control the fire or safely escape.

Self-Test & Silent Function

Equipped with a low-battery warning, which easily informs you when it's time to replace the battery. Comes with silent mode that allows you to avoid false alarms from cooking or steamy showers. Once pushed, silent mode is activated for only 8 minutes, then returns to normal functionality, thus keeping you and your family safe.

Guaranteed Quality

This smoke detector complies with the EN 14604 standard, ensuring high quality and durability for home safety.

Protects Your Family

Place the smoke detector in anywhere you want to enhance the safety of your family; watches over you around the clock.



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.



LED Indicators:

States	LED Indication
Normal	Blinking red once every 32 seconds
Test/Alarm	The red LED will blink once per second; it will continue until the air is cleared or the test button is pushed
Silent Mode	The red LED will flash once every 8 seconds after pressing the test/silence button, the device is muted for 8 mins.
Low battery	Blinking red once every 32 seconds, short and quick beeps
Malfunction	The alarm chirps between two flashes every 32 seconds

Specifications:

Power	DC 9 V Carbon Zinc or Alkaline battery
Sensor Type	Photoelectric
Standby Current	<15 μ A
Alarm Current	<25 mA
Alarm Volume	>85 dB(A) at 3 meters
Alarm Sensitivity	0,100–0,160 dB/m
Operating Temperature	0–40 °C
Operating Humidity	<93 % RH (no condensation)
Storage Temperature	5–28 °C
Storage Humidity	30–70 %
LED Indicator	Yes
Silent Mode Time	Approx. 8 minutes
Mounting Methods	On wall or ceiling
Dimensions	Ø10x3,45 cm
Weight	115 g

Package Contents:

- » 1x Smoke Detector
- » 1x 9 V Battery
- » 1x Mounting Kit
- » 1x User Manual

Package Information:

- » Packing Dimension: 104x104x50 mm
- » Packing Weight: 0,16 kg
- » Carton Dimension: 460x280x385 mm
- » Carton Q'ty: 60 pcs
- » Carton Weight: 10,6 kg



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.

