



ITEM NO.	COLOR
723193	GREY
723194	BLACK

Specification:

Material:

- 1.Metal frame: SPCC.
- 2. Plastic Housing :ABS
- 3.RJ45 contact material & finished:
 - 3-1.Phosphor Bronze with Nickel plated.
 - 3-2.Contact area : Gold plated.

4.IDC Housing: PC

5.IDC Terminal material & finished:

- 5-1.Phosphor Bronze with Tin plated.
- 5-2. Krone tool compatible.
- 5-3. Suitable for 22-26 AWG stranded and solid wire.

Performance:

- a.The sticker color codes combine two wirings of T568A & T568B.
- b.Insertion Force: 900 gms for 8 contacts.
- c.Retention Strength: 7.7 kgs between Jack and Plug.
- d.Operation Temperature: -30, to 60, .
- e.Durability:
 - e-1. Jack : 750 cycles Plug-Jack mating and unmating test, Insertion cycles at 20 cycles/minute max. Contact resistance test per 100 cycles.
 - e-2. IDC : Max. 200 punching times.
- f.The Cat.5e performance is in compliance with the ANSI/TIA/EIA 568 C.2 standard.

		Tolerance: X. ±0.5 .X ±0.3 .XX ±0.10		SCALE: FREE	CUSTOMER:		Approved by	
		Angle: X° ±3° .X° ±1°		UNIT: mm	CUSTOMER P/N:		COMPANY P/N:	
REV.		DESCRIPTION		REV.: 00	DWG. No.:		TITLE: 8 PORT PANTCH PANEL (CAT6)	
DATE		SHEET 1/1		Checked by		Design by XJH		