



Vcc	
D-	
D+	
GND	
Screen	

  

Nr. / No.	Länge / Length (m)	Farbe / Color
50953	1.80	
50954	3.00	
50955	5.00	
68606	1.00	
68900	1.80	
68901	3.00	
68902	5.00	
68972	1.80	
68973	3.00	
68974	5.00	
96185	1.00	
96186	1.00	
96187	1.80	
96188	3.00	
96189	5.00	

- USB 2.0 Kabel; lose Ware
  - Verbinders: USB-A St. > USB-B St.
  - USB Standard: High Speed USB 2.0
  - Datenrate: max. 480 Mbit/s
  - Innenleiter: AWG 28 (7/0.12 BC)\*  
\*(kann zwischen AWG 28 und 2xAWG28+2xAWG30 variieren)
  - Schirmung: doppelt (AL-Folie+Geflecht)
  - Isolierung: PVC
  - RoHS-konform
- USB 2.0 cable; bulk
  - Connectors: USB-A plug > USB-B plug
  - USB Standard: High Speed USB 2.0
  - Data rate: max. 480 Mbps
  - inner conductor: AWG 28 (7/0.12 BC)\*  
\*(may vary between AWG 28 and 2xAWG28+2xAWG30)
  - Shielding: double (AL foil + braid)
  - Insulation: PVC
  - RoHS compliant

Änderungen		Datum	Name	Bezeichnung	Blatt
Datum	Name	gez.:	13.11.2015	USB AB HiSpeed 2.0	
		gepr.:	13.11.2015		
		Norm:		Zeichnungs-Nr.:	von
Änderungen vorbehalten / Subject to change					

