



**SAT-Koaxialkabel 1,0 / 4,6, BZE - CE, DIGITAL > 120 dB, 4-fach geschirmt**  
**SAT-coaxial cable 1.0/4,6, 4times shielded**

BZT G 686 556 B

Innenleiter / <i>inner conductor</i>	Ø 1,0 mm	
Material Innenleiter / <i>material conductor</i>	Staku / CCS	
Dielektrikum / <i>isolation</i>	Ø 4,6 mm	
Material Dielektrikum / <i>material isolation</i>	Foam PE	
Aufbau / <i>Specification</i>	1x Alufolie-einfach kaschiert	
	1x 80x0,12 mm Alu	
	1x Alufolie-einfach kaschiert	1x 64x0,12 mm Alu
Außenmantel / <i>jacket</i>	Ø 7,2 mm	
Materialfarbe / <i>material colour</i>	PVC / weiß / <i>white</i>	
Wellenwiderstand / <i>impedance</i>	75 Ω	
Schirmungsmaß / <i>screening factor</i>	> 120 dB	
Kapazität ca. / <i>Capacitance</i>	ca. 55pF/m	
Verkürzungsfaktor v/c / <i>Velocity ratio v/c</i>	0,82	
Biegeradius / <i>Bending radius</i>	45 mm	

**DÄMPFUNG bei 20 oC dB/100 m / *attenuation at 20 oC dB/100 m:***

100 MHz	3,9
200 MHz	5,8
500 MHz	11,7
800 MHz	13,1
1.000 MHz	16,5
1.750 MHz	24,2
2.050 MHz	27,6
2.250 MHz	28,1
2.400 MHz	29,5