




ITEM NO.	COLOR
723214	BLACK



Specification:

Material:

- 1. Metal frame: SPCC.
- 2. Plastic Housing :ABS
- 3. RJ45 contact material & finished:
 - 3-1. Phosphor Bronze with Nickel plated.
 - 3-2. Contact area : Gold plated.


- 4. IDC Housing: PC
- 5. IDC Terminal material & finished:
 - 5-1. Phosphor Bronze with Tin plated.
 - 5-2. Krone tool compatible.
 - 5-3. Suitable for 22-26 AWG stranded and solid wire.

Performance:

- a. The sticker color codes combine two wirings of T568A & T568B.
- b. Insertion Force: 900 gms for 8 contacts.
- c. Retention Strength: 7.7 kgs between Jack and Plug.
- d. Operation Temperature: -40° to 68° .

e. Durability:

- e-1. Jack : 750 cycles Plug-Jack mating and unmating test, Insertion cycles at 20 cycles/minute max. Contact resistance test per 100 cycles.
- e-2. IDC : Max. 200 punching times.
- f. The Cat.6 performance is in compliance with the ANSI/TIA/EIA 568 C.2 standard.

			Tolerance: X. ±0.5 .X ±0.3 .XX ±0.10	SCALE: FREE	CUSTOMER:		Approved by		
			Angle: X° ±3° .X° ±1°	UNIT: mm			CUSTOMER P/N:	COMPANY P/N:	Checked by
REV.	DESCRIPTION	DATE	REV.: 00	REV.: 00			DWG. No.:	TITLE: 24 PORTS CAT6 SHIELDED PATCH PANEL	Design by XJH
1		2	3	4	5	6	7		