

LogiLink®

3x1 HDMI™ Switch 1080p/60 Hz

Art. No.: HD0042



Designed for applications that require the routing of 3 sources to 1 compatible display device. It enables the reliable transmission at video resolutions up to 1080p@60 Hz. Features auto and manual switching modes for selection; instantly switching for a smooth video transition between HDMI ports.

Features:

- » Allows up to three HDMI sources to be connected to one HDMI display
- » Supports manual switching, remote switching or automatic switching
- » Resolution up to Full HD 1080p@60 Hz
- » Bandwidth: 2.5 Gbps/250 MHz per Channel
- » Supports 3D and HDCP pass-through
- » Supports Consumer Electronics Control (CEC)
- » Supports 12bit per channel (36bit all channels) deep color
- » Supports uncompressed audio such as LPCM
- » Supports compressed audio such as DTS, Dolby Digital (including DTS-HD Master Audio™ and Dolby TrueHD)



- (a) HDMI input 1-3 LED Indicators
- (b) Select button to choose between the video source
- (c) HDMI output port
- (d) DC 5 V input
- (e) IR receiver input port
- (f) HDMI input 1-3 ports

*Power adapter is not included; 5 V/500 mA or above is required for the power adapter.



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.

Specifications:

| | |
|-----------------------------|--|
| Input Ports | 3x HDMI-A female, 1x 3.5mm jack for IR |
| Output Port | 1x HDMI-A female |
| HDMI Version | 1.3 |
| HDCP Version | 1.3 |
| HDMI CEC | Yes |
| Output Resolution | 480i/60 Hz, 576i/50 Hz, 1080i/50/60 Hz, 480p/60 Hz, 576p/50 Hz, 720p/50/60 Hz, 1080p/24/25/30/50/60 Hz |
| Video Bandwidth | 2.5 Gbps/250 MHz |
| 3D Supporting | Yes |
| Input and output DDC signal | Yes |
| Chassis Material | ABS |
| LED Indicator | Yes |
| IR Remote Support | Yes |
| Power Consumption | 5 W max. |
| Uncompressed Audio | LPCM 7.1 |
| Compressed Audio | DTS, Dolby Digital, DTS-HD Master Audio™, Dolby TrueHD |
| Operating Temperature | 0°C–70°C |
| Operating Humidity | 10%–85% RH (no condensation) |
| Storage Temperature | -10°C–80°C |
| Storage Humidity | 5%–90% RH (no condensation) |
| Dimensions | 8x5.8x1.8 cm |
| Weight | 0.054 kg |

Package Contents:

- » 1x 3x1 HDMI Switch
- » 1x Remote Control
- » 1x IR Receiver
- » 1x User Manual

Package Information:

- » Packing Dimension: 160x107x50 mm
- » Packing Weight: 0.16 kg
- » Carton Dimension: 575x255x345 mm
- » Carton Q'ty: 40 pcs
- » Carton Weight: 7.2 kg



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.



Made in China