

# LogiLink®

## 4K HDMI™ HDBaseT KVM Extender Set, 100 m


Art. No.: HD0029



This 4K HDMI HDBaseT KVM Extender Set utilizes HDBaseT technology to extend 4K HDMI audio/video signal over a networking cable, up to 100 m. It also supports USB2.0 connection and access up to 6 connected USB devices.

### Features:

- » Supports HDBaseT 2.0 over a single CAT5e/6/7/8 cable up to 100 m
- » Resolution up to UHD 4K@60 Hz (YCbCr 4:2:0) and Full 3D
- » Bandwidth: 3.4 Gbps/340 MHz per Channel (10.2 Gbps total)
- » Supports HDCP 2.2
- » Supports DDC, HDR, CEC and USB 2.0 control for KVM function
- » Supports uncompressed audio such as LPCM 7.1
- » Supports compressed audio such as DTS, Dolby Digital (including DTS-HD Master Audio™ and Dolby TrueHD)
- » Compatible with Windows, Mac OS and Linux OS
- » Plug and Play, no software installation required




- (a) Connect to HDBaseT receiver with a Cat.5e/6/7 cable
- (b) Connect to input sources via HDMI male input port
- (c) USB-B female port: connect to PC or laptop for data transmission
- (d) Connect to DC 12 V Power Supply
- (e) 6x USB 2.0 type A ports: Connect to the USB-enable devices
- (f) Connect to HDBaseT transmitter with a Cat.5e/6/7 cable
- (g) Connect to output devices (HDMI TV/monitor) via HDMI male output port
- (h) Audio port: connect to stereo audio output device
- (i) Microphone port: connect to microphone audio input device



\*The specifications and pictures are subject to change without prior notice.  
\*All trade names referenced are the registered trademarks of their respective owners.





## Specifications:

|                                    |   |
|------------------------------------|---|
| Transmitter (TX) Interface         | 1x RJ45 Jack, 1x HDMI-A female, 1x USB-B female, 1x DC power jack   |
| Receiver (RX) Interface            | 1x RJ45 Jack, 1x HDMI-A female, 6x USB-A female, 1x DC power jack, 2x 3.5mm Audio Jack  |
| HDMI Version                       | 2.0   |
| HDCP Version                       | 2.2   |
| Working Distance                   | 100 m   |
| HDBase-T Technology                | Yes   |
| Output Resolution                  | 480i/60 Hz, 576i/50 Hz, 1080i/50/60 Hz, 480p/60 Hz, 576p/50 Hz, 720p/50/60 Hz, 1080p/24/25/30/50/60 Hz, 4K@30Hz with YCbCr 4:4:4 and 4K@60Hz with YCbCr 4:2:0 |
| Video Bandwidth                    | 3.4 Gbps/340 MHz  |
| CEC (Consumer Electronics Control) | Yes   |
| HDR (High-Dynamic Range)           | Yes   |
| DDC (Display Data Channel)         | Yes   |
| LED Indicator                      | Yes   |
| Chassis Material                   | Metal   |
| 3D Supporting                      | Yes   |
| KVM Support                        | Yes   |
| Power Consumption                  | TX:3 W, RX:7 W  |
| Power Supply                       | 12 V/2 A  |
| Uncompressed Audio                 | LPCM 7.1  |
| Compressed Audio                   | DTS, Dolby Digital, DTS-HD Master Audio™, Dolby TrueHD  |
| Networking Cable                   | Cat5E/6/7/8   |
| Operating Temperature              | 0°C–70°C  |
| Operating Humidity                 | 10%–85% RH (no condensation)  |
| Storage Temperature                | -10°C–80°C  |
| Storage Humidity                   | 5%–90% RH (no condensation)   |
| Dimensions                         | TX:10.4x8.9x2.6 cm ; RX:10.8x8x2.8 cm   |
| Weight                             | TX:0.235 kg; RX:0.26 kg   |



RoHS  
compliant



\*The specifications and pictures are subject to change without prior notice.  
\*All trade names referenced are the registered trademarks of their respective owners.



HD0029



4 052792 050752

Made in China

## Specification of External Power Supply:

|               |                                 |
|---------------|---------------------------------|
| Input Voltage | 100–240 V, 50/60 Hz 0.65 A max. |
| Output Power  | 12 V/2 A, 24 W                  |
| DC Plug       | 5.5x2.1 mm                      |
| Dimensions    | 68x43x68 mm                     |
| Cable Length  | 1.2 m                           |
| Weight        | 0.12 kg                         |



## Package Contents:

- » 1x HDMI Extender Set
- » 4x Mounting Ears
- » 2x Power Adapters 12 V/2 A
- » 1x User Manual

## Package Information:

- » Packing Dimension: 243x196x60 mm
- » Packing Weight: 0.92 kg
- » Carton Dimension: 505x235x340 mm
- » Carton Q'ty: 10 pcs
- » Carton Weight: 9.8 kg



\*The specifications and pictures are subject to change without prior notice.  
\*All trade names referenced are the registered trademarks of their respective owners.

