

# LogiLink®

## 4K HDMI™ Splitter/Switch 3-Port Bidirectional 4K/30 Hz


Art. No.: HD0040





Allows you easily switch three HD Sources to one HDMI-enabled display or split one HD Source to three HDMI-enabled displays. This newer bi-directional switch adopts integrated IC solution to substantially reduce product power consumption for improved compatibility.

### Features:

- » Bidirectional 3 to 1 HDMI switch and 1 to 3 HDMI Splitter, Pigtail type
- » Resolution up to UHD 4K@30 Hz and Full 3D
- » Bandwidth: 3.4 Gbps/340 MHz per Channel (10.2 Gbps total)
- » Supports 16 bit per channel (48 bit all channels) deep color
- » Supports HDCP 1.4, DDC and CEC functions
- » Supports uncompressed audio such as LPCM
- » Supports compressed audio such as DTS, Dolby Digital (including DTS-HD Master Audio™ and Dolby TrueHD)



- (a) HDMI input/output 1-3 ports
- (b) Select button to choose between the input and output source/display
- (c) USB power input
- (d) HDMI input/output 1-3 ports LED



\*The specifications and pictures are subject to change without prior notice.  
\*All trade names referenced are the registered trademarks of their respective owners.

## Specifications:

Interface	1x HDMI-A male, 3x HDMI-A female, 1x Mini USB female for power
HDMI Version	1.4
HDCP Version	1.4
Output Resolution	480i/60 Hz, 576i/50 Hz, 1080i/50/60 Hz, 480p/60 Hz, 576p/50 Hz, 720p/50/60 Hz, 1080p/24/25/30/50/60 Hz, 4K@24/25/30 Hz
Video Bandwith	3.4 Gbps/340 MHz
CEC (Consumer Electronics Control)	Yes
DDC (Display Data Channel)	Yes
LED Indicator	Yes
Chassis Material	ABS
3D Supporting	Yes
Power Consumption	5 W max.
Uncompressed Audio	LPCM 7.1
Compressed Audio	DTS, Dolby Digital, DTS-HD Master Audio™, Dolby TrueHD
Operating Temperature	0°C–70°C
Operating Humidity	10%–85% RH (no condensation)
Storage Temperature	-10°C–80°C
Storage Humidity	5%–90% RH (no condensation)
Dimensions	8.2x6.1x1.5 cm
Weight	0.091 kg

## Package Contents:

- » 1x 4K HDMI Splitter/Switch
- » 1x USB Charging Cable
- » 1x User Manual

## Package Information:

- » Packing Dimension: 190x145x60 mm
- » Packing Weight: 0.234 kg
- » Carton Dimension: 505x235x340 mm
- » Carton Q'ty: 15 pcs
- » Carton Weight: 4.1 kg



\*The specifications and pictures are subject to change without prior notice.  
\*All trade names referenced are the registered trademarks of their respective owners.

