

Model:		
IP-SPS02-TY		* 2 M P Camera (No TF Card) X 1 * Instructions X1 * Screw bag X1
Packing box size(mm)/weight(kg)		1 Pcs : 222*200*125; 0.8 kg
Outer box size(mm)/weight(kg)		20 Pcs/box :470*420*650; 16.04 kg
Specification parameter		
system	Main Processor	GK7102C
	image sensor	GC2053H
	Operation System	Embedded LINUX OS system
Video	High Definition	2MP
	Video Compression	Smart H.264
	Rotation angle	Horizontal:355° ; vertical: 90°
	Object tracking	Support
	low illumination	0.1LUX/F1.2
	picture Capture	Support
	Video Flip	Support
Audio	Coding standard	G.711
	Two-way Speech	Support
Record management	Video file size	2.5GB-4.5GB/Day
	Record Mode	Manual record, motion detection record, scheduled record, alarm
	Video storage	TF Card/Cloud
	playback, back up	Support
	Alarm trigger	Video Push、Alarm recording、screen shot capture ,sending Email
Network	Network Interface	1*RJ45 , 10/100M10-100 Base-T, self-adaptable Ethernet port
	WIFI	802.11b/g/n
	Bitstream	Three Stream
	Network Protocol	Support TCP/IP、 RTSP、 ONVIF, etc
	transmission mode	P2P、 Smart Cloud Sever
	WIFI connection	Sweep QR code, Network Cable connection, AP Hotspot Addition
extend	TF Card	Maximum support 128GB TF card
	Reset key	Support
power supply	Power	DC 12V 2A
	Power consumption	10W
work environment	Suitable place	Home、 shop、 School、 factory;
	Installation mode	Flat put、 Wall mounted、 hoisting
	Working	-10℃ — +55℃
	Working humidity	10% — 90%
Other	Camera lens	3.6MM
	Lamp board	8 pcs
	Product size	(mm)

