



**PRIME**  
FANLESS TITANIUM



**SPECIAL FEATURES**

- ❖ Ultra High Efficiency, 80 PLUS® Titanium Certified
- ❖ Fully Modular Cabling Design
- ❖ Seasonic Fanless Design
- ❖ Micro Tolerance Load Regulation (MTLR) [0.5 %]
- ❖ DC to DC Converter Design

**POWER DISTRIBUTION**

Model	+3.3 V	+5 V	+12 V	-12 V	+5 Vsb	Total Power
SSR-600TL	20 A	20 A	50 A	0.3 A	3 A	600 W
	100 W		600 W	3.6 W	15 W	



**WIRE CONFIGURATION**

Cable						
Model	Main Power (24P / 20P) 610 mm	EPS 12 V / ATX 12 V (8P / 4P) 650 mm	PCI-E (8P / 6P)	SATA	Peripheral (4P)	FDD (4P)
SSR-600TL	1	2	4	6	5	1



Safety & EMI / EMC

Protection Features: OPP / OVP / UVP / SCP / OCP / OTP

Dimensions: 170 mm (L) x 150 mm (W) x 86 mm (H)



Specifications may change without prior notice



**Headquarters** sales@seasonic.com  
**USA** ssa.sales@seasonic.com  
**Europe** sse.sales@seasonic.com

www.seasonic.com