

Flat Satellite Antenna

Make it easy for yourself..

- Flat design
- Works on Ku-band satellite
- Dual Linear Polarization (Vertical & Horizontal)
- Installation brackets included (adapted by special bracket to adjust skew angle)



Single LNB



Twin LNB



Quad LNB



Easy to install

Balcony type



Wall type



Specification

Input Satellite Frequency	10.7~12.75GHz
Polarization	Vertical & Horizontal
Antenna Gain	33.7 dBi @ 12.7 GHz
Size(W×D×H)	517×277×58mm
Weight	4.5kg
Current Consumption	150mA (max)
Operating Temperature	-30°C to +60°C
Storage Temperature	-40°C to +80°C
LNB output	Single:1 / Twin: 2 / Quad : 4
Changeover Low / High	0KHz / 22KHz
LNB Output Frequency	950~1,950MHz / 1,100~2,150MHz
L.O. Frequency	9.75GHz / 10.6GHz
LNB Noise Figure at 25°C	0.2 dB Typical
Input VSWR	2.5 : 1 Typical
Output VSWR	2.5 : 1 Typical
Conversion Gain	60 dB Typical
Gain flatness	6dB p-p (max)
Power supply	12~14V DC (Vertical)
	16~19V DC (Horizontal)

Window type



Stand type

