



PRIME GX

SPECIAL FEATURES

- ❖ High Efficiency, 80 PLUS® Gold Certified
- ❖ Fully Modular
- ❖ Compact ATX Size [140 mm deep] *
- ❖ Top-Quality 135 mm Fluid Dynamic Bearing Fan
- ❖ Premium Hybrid Fan Control
- ❖ Micro Tolerance Load Regulation (MTLR) [0.5 %]
- ❖ Super Low Ripple Noise [under 20 mV]
- ❖ Cable-free Connection Design
- ❖ Gold Plated High Current Terminal (MB, CPU and PCIe)
- ❖ Multi-GPU Technology Support

* for 750 W, 650 W,



POWER DISTRIBUTION

Model	+3.3 V	+5 V	+12 V	-12 V	+5 Vsb	Total Power
PRIME GX-1000	25 A	25 A	83 A	0.3 A	3 A	1000 W
		125 W	996 W	3.6 W	15 W	
PRIME GX-850	20 A	20 A	70 A	0.3 A	2.5 A	850 W
		100 W	840 W	3.6 W	12.5 W	
PRIME GX-750	20 A	20 A	62 A	0.3 A	2.5 A	750 W
		100 W	744 W	3.6 W	15 W	
PRIME GX-650	20 A	20 A	52 A	0.3 A	3 A	650 W
		100 W	648 W	3.6 W	15 W	



CONNECTOR QUANTITY

Model	Cable					
	Main Power (24P / 20P) 610 mm	EPS 12 V / ATX 12 V (8P / 4P) 650 mm	PCI-E (8P / 6P)	SATA	Peripheral (4P)	FDD (4P)
PRIME GX-1000	1	2	6	14	5	1
PRIME GX-850	1	2	6	14	5	1
PRIME GX-750	1	2	4	10	3	1
PRIME GX-650	1	2	4	10	3	1



Safety & EMI / EMC

Protection Features: OPP / OVP / UVP / SCP / OCP / OTP

Dimensions: 170 mm (L) x 150 mm (W) x 86 mm (H) (1000 W, 850 W)
140 mm (L) x 150 mm (W) x 86 mm (H) (750 W, 650 W)



Specifications may change without prior notice



Headquarters sales@seasonic.com
USA ssa.sales@seasonic.com
Europe sse.sales@seasonic.com