

## F9

### 600Mbps Whole-Home Coverage Wi-Fi router

F9 is a 600Mbps High Speed and whole-home coverage Wi-Fi router. The wireless transmission rate of F9 is up to 600Mbps. Compared to 450Mbps and 300Mbps products, it's transmission is more efficient and smooth, support more equipments connection at the same time. Its built-in signal amplifiers, Beamforming technology, and four external antennas offer you lag-free gaming and uninterrupted video streaming experience. F9 also provides the Smart WiFi Schedule function, which automatically turns on/off WiFi to reduce power consumption and bring smart internet connectivity to your family.



### 600Mbps for super fast experience

33% faster than 450Mbps router, F9 allows you to enjoy much faster internet experience



### Powerful coverage & wall penetration

Four external 6 dBi antennas and Beamforming+ technology ensure powerful coverage and wall penetration for small and medium apartments



### Smart app for convenient remote management

Tenda app allows users to remotely manage the devices connected to it and blacklist the unauthorized users with a single tap

## Features

- Transfer rate up to 600Mbps
- Four external 6 dBi antennas
- Management with Tenda App
- Support WiFi Turn on/off
- Support wireless signal repeater and WISP

## Specifications

Hardware Specifications	
Wired Communications Standards	IEEE b/g/n,IEEE 802.3/3u
Interface	1*10/100Mbps WAN port, 3* 10/100Mbps LAN ports
Antennas	External 6 dBi omnidirectional antenna × 4
Button	1*WPS/RST,1*WIFI
Power Supply	Input:100-240V-50/60Hz,0.3A Output:DC 9V==0.6A
Dimensions	171.3mm*171.3mm*36.4mm
LED Indicator	System×1; WiFi ×1; LAN×3; WAN ×1; WPS ×1
Wireless Features	
Wireless Communications Standards	IEEE802.11b,IEEE 802.11g, IEEE 802.11n
Data Rate	802.11b : 11 Mbps 802.11g : 54 Mbps 802.11n : 450Mbps 802.11n (256QAM): 600Mbps
Frequency	2.400 – 2.4835 GHz
EIRP Power (Max.)	2.400 – 2.4835 GHz: 19.65 dBm (EIRP)
Wireless Security	Encryption Mode:WPA2-PSK WPA Algorithm:AES, TKIP, TKIP&AES
Software Features	
Standard Version	RFC768 UDP RFC791 IP RFC792 ICMP RFC793 TCP Channel Bandwidth: 20MHz, 20/40MHz
DHCP Server	Support
Working Mode	Router, WISP, Universal repeater, AP
System Tool	Internet time,Backup/Recovery,Upgrade; Reset to Factory Default; Login Password; System Log; Reboot
Special Features	Smart WiFi schedule Smart power saving Smart LED schedule Tenda Cloud Tenda APP

## Specifications

Temperature	Operating Temperature:0°C~40°C Storage Temperature:-40~70°C
Humidity	Operating Humidity:10%~90%, non-condensing Storage Humidity:5%~90%, non-condensing
Default Login Domain Name	tendawifi.com
Packing List	1 * 600Mps Wireless N Router 1 * Quick Installation Guide 1 * Power Adapter 1 * Ethernet Cable

### SHENZHEN TENDA TECHNOLOGY CO.,LTD.

Tenda Technology Bldg.Int'l E-City,  
#1001 Zhong Shan Yuan Rd.,Nanshan District,Shenzhen China.

Tel:+86-755-2765 7098

Fax:+86-755-2765 7178

PC:518055

Specifications are subject to change without notice. Copyright ©2017 SHENZHEN TENDA TECHNOLOGY CO.,LTD. All rights reserved. Tenda is the trademark of SHENZHEN TENDA TECHNOLOGY CO.,LTD. All other brand names mentioned herein are the trademark or registered trademarks of their respective holders.